

TECHNICAL DATA SHEET

产品说明书

GYMCOL ADHESIVES (PINGHU) Co., Ltd

2008 Xinqun Road, Economic Development Zone Pinghu, Zhejiang, China. 金固牢胶粘剂 (平湖) 有限公司 中国浙江平湖经济开发区新群路 2008 号.

Version 版本: 3

Edition 编辑: 2015-07-18

Page 页码 1/1

PRODUCT CODE: XC-1104B Polyurethane Emulsion Adhesive

产品名称: XC-1104B 乳液型聚氨酯胶粘剂

A Polyurethane Emulsion adhesive has high adhesion to many substrates, can form a transparent flexible film after cured.乳液型聚氨酯胶粘剂它可以粘接许多材料,在使用后可以形成透明柔软的薄膜。

MAIN APPLICATIONS 主要应用

Adhesive especially designed in wet bonding adhesive applications with good open time. This product has excellent adhesion to PVC; bonding films and panel like PU, PS, ABS, fiberboard and PP,PE and TPO after pretreatment .It can be mixed with Cross-linking Agent. This formula is recommended for the automotive flocking application .This adhesive has strong bonding . 这个胶粘剂在合适的开放时间下粘接.它可以粘接 PVC,PU,PS, ABS, 纤维板以及经过预处理的 PP, PE 和 TPO 等材料.和固化剂配合使用,是一款具有高粘接强度的产品。适用于汽车植绒工艺。

Made thinking in friendly environment.

环保理念

Solubility 可溶性

It can be soluble into high polar solvent.

可溶于高极性溶剂

PRODUCT SPECIFICATIONS 产品指标

Property	Specifications
Viscosity Brookfield, cp @ 25 °C 粘度	2000-4000
Solid content, % 固含量	48-51
Density, g/cc 比重	1.04 - 1.10
*Open time, min 开放时间	1-3
*Color	Milky white 奶白色

^{*} Typical value

Storage Conditions

This product not contains volatile solvent. It doesn't flammable. Keep in dry place between 15 - 25 °C. In this conditions the validate time is up to 12 months.

该产品不含挥发性溶剂,不可燃,干燥条件 15~25°C,保质期为 12个月.

Designed by:

José Ramón Cerezo Technical Director GSA Approved by:

Cai Ping Chen

Cai Ping Chen Technical and R&D Manager GYMCOL China